



PRODUCT DATA SHEET

Multi-Vehicle ATF

Product Description:

Formulated with synthetic base stocks and premium performance additives, **Viscosity1 MULTI-VEHICLE ATF** is a premium grade low viscosity synthetic automatic transmission lubricant. This product contains a premium performance additive package designed for excellent oxidation stability and thermal resistance as well as excellent friction modification properties. **Viscosity1 MULTI-VEHICLE ATF** is a multipurpose automatic transmission lubricant which is suitable for use in applications which require GM DEXRON® VI as well as a variety of North American, Asian and European passenger car applications requiring low viscosity ATF.

Typical Properties:*

<i>Parameter</i>	<i>Result</i>
Appearance, Visual	Red, Dyed Liquid
Viscosity @ 40°C, cSt, ASTM D445	29.5
Viscosity @ 100°C, cSt, ASTM D445	6.0
Viscosity Index, ASTM D2270	155
Brookfield Viscosity @-40°C, ASTM D2983, cP	12,000
Flash Point, °C, ASTM D92	190
Pour Point, °C, ASTM D97	-52

**The values shown are typical of current production. Some are controlled in the manufacturing process, while other are not. All of them may vary within tolerable ranges.*

Suitable for Use:

- Ford MERCON®*, MERCON® V*, MERCON® SP*, MERCON® LV*
- General Motors DEXRON®-II(E), DEXRON-III(G,H), DEXRON-VI
- BMW LT 71141, LA2634, M-1375.4, 7045-E, ETL-8072B •Chrysler ATF +3 (SM7176-E)*, ATF +4 (MS9602)*
- Aisin Warner AW-1
- Honda/Acura DW-1, ATF-Z1
- Hyundai/Kia/Mitsubishi Diamond SP, SP-II, SP-III
- Isuzu ATF-II, ATF-III, Genuine ATF
- Mazda ATF 3317, F-1, FZ/S-1/N-1, M-III, M-V
- MB 236.12*, MB 236.14*, MB 236.15*
- Nissan 402, Matic D/J/K/S
- Allison TES-389*, C-4
- Hyundai/Kia SP-IV, SPH-IV/SP4-M
- Idemitsu ATF HP, K17
- JASO M315 Class 1A* and 2013, 1A-LV
- MB 236.41/5/6/7/8/9/10/11, NAG-1
- Mitsubishi ATF-J2, ATF-J3
- Subaru ATF, ATF 5AT, ATF-HP

